

**SURFACE PREPARATION:**

The surface should be clean, dry & free of any foreign matter. Spray Graffiti Gard to any surface & let dry. Some surfaces may require more than one application. The product may be applied at 40°F and above. Make sure there is no frozen moisture in or on the substrate. Product must be applied to a dry surface. Always apply to test area before proceeding with application.

**APPLICATION & MAINTENANCE INSTRUCTIONS:**

Graffiti Gard will darken porous surfaces. Test in inconspicuous area before application. Coated surfaces may be washed with water or mild detergent.

**APPLICATION INSTRUCTIONS:**

1. Shake can well prior to application.
2. Maintain a maximum of 8 inches away from the surface to be sprayed. Use a flood coat & apply liberally.
3. Allow a minimum of 30 minutes to 1 hour before reapplication.
4. A single coat may be sufficient, but a second or third coat can be applied depending on your application & requirements.

**Purge nozzle after use: Hold can upside down and spray to flush nozzle and prevent clogging.**

**GRAFFITI REMOVAL:**

Success has been achieved with a dry paper towel, dry soft abrasive material or by using tape to pull off graffiti off. Wipes can also be used as they have no effect on Graffiti Gard. Any light alkaline or citrus cleaner can be used. Pressure washing under 1000 psi will also remove graffiti. Pressure over 1000 psi may damage coating.

**\* Always test chemical cleaners & removal methods of choice before moving into a full application.**

**COVERAGE:**

One can of Graffiti Gard can cover approximately 30 square feet depending on the substrate. Please see the Production Data Sheet for information regarding coverage on different substrates.

**DANGER:** Extremely Flammable. Contents under pressure. Do not use near fire or sparks. Do not puncture or incinerate container. Exposure to temperatures above 120°F may cause bursting. Never throw can into fire or incinerator.

**FIRST AID:** Wash skin with soap & water & rinse immediately. Wash and flush eyes for 15 minutes. If irritation persists call a physician. If swallowed, Do not induce vomiting and call a physician.

**KEEP OUT OF THE REACH OF CHILDREN.**

TO REORDER CALL:  
SYNDYX  
(800) 525-5615

# GRAFFITI GARD

## Graffiti Prevention

### ANTI-STICK PROPERTIES PROTECT ANY SURFACE 100% CLEAR

**GRAFFITI GARD** is an anti-stick coating that is unique & permanent. Graffiti Gard bonds to all substrates and will not allow paint, marker, stickers or other forms of graffiti to adhere. It is clear and UV stable. Graffiti Gard dries fast and forms a chemical resistant anti-stick film. Graffiti Gard allows for expansion & contraction, building movement and temperature extremes. This product is environmentally friendly, non-reactive, VOC & AQMD compliant.

**DANGER : EXTREMELY FLAMMABLE  
KEEP OUT OF REACH OF CHILDREN. VAPOR MAY  
BE HARMFUL. CONTENTS UNDER PRESSURE.  
SEE OTHER CAUTIONS ON BACK PANEL**

**NET WT. 12 OZ.**

